

VYSOTSKIY, Yu.L. (g.Chelyabinsk)

Train and locomotive traffic control in the operation of lengthened
hauling distances. Zhel.dor.transp. 43 no.4:38-41 Ap '61.

(Railroads--Management)

(MIRA 14:3)

VYSOTSKIY, Yu.L., inzh.

Establishing operative norms for train movements under the
conditions of considerable fluctuations in the traffic volume.
Trudy NIIZHT no.25:165-173 '61. (MIRA 16:11)

FILIPPOV, M.P.; VYSOTSKIY, Yu.L.

Cuvette for luminescent analysis at low temperatures. Zav.
lab. 29 no.9:1147-1148 '63. (MIRA 17:1)

1. Lisichanskiy filial Gosudarstvennogo instituta azotnoy
promyshlennosti.

VYSOTSKIY, Yu.L. (g. Chelyabinsk).

Operational planning of train work with the new types of traction.
Zhel. dor. transp. 40 no.12:72-73 D '58. (MIRA 12:3)

1. Starshiy dispatcher otдела ekspluatatsii Chelyabinskogo otdeleniya.
(Railroads--Management)

BODYAKO, M.M. [Badziaka, M.M.]; VISOTSKIY, Yu.M. [Vysotski, IU.M.]

Problem of temperature control in induction heating. Vestsi
AN BSSR.Ser.fiz.-tekh.nav. no.4:52-56 '58. (MIRA 12:4)
(Temperature regulators) (Induction heating)

VYSOTSKIY, Z. Z.

PA 245116

USSR/Chemistry - Adsorption, Alumina--
Silica Gel Jan 53

"The Effect of the Conditions of Preparation of Alumina-Silica Gel on Its Structure and Sorption Properties," I. Ye. Neymark, Z. Z. Vysotskiy, Inst of Phys Chem imeni L. V. Prsazhevs'kiy, Acad Sci Ukrainian SSR

"Dopovid i Ak Nauk Ukrain's'koi RSR" No 1, pp 17-20

The effect of conditions of preparation of alumina silica gel on its structure, composition, and sorption properties was studied. Results indicate that the pore structure and sorption properties differ from

245116

that of the starting material. In an acid medium, small additions of $Al(OH)_3$ to silicic acid sol lead to the formation of an alumina-silica gel with finer pores and greater specific surface than that of the original gel. In neutral and alkaline media, the silica gels are coarser than the control sample of alumina gel. It was demonstrated that the rules for the formation of the pore structures previously established for silica gel could be extended to mixed hydrophylic sorbents of the alumina-silica gel type if the characteristics due to the second component are taken into account. Presented by A. I. Brodskiy, Acting Mem, Acad Sci Ukrainian SSR.

245116

VYSOTS'KYY, Z.Z.; NEYMARK, I.Ye.; BRODS'KYY, O.I., diysnyy chlen.

Applicability of the mechanism forming the porous structure of hydrophilic gells of mixed sorbents. Dop. AN URSR no. 5:333-336 '53. (MLRA 6:10)

1. Akademiya nauk Ukrayins'koyi RSR (for Brods'kyy). 2. Instytut fizychnoyi khimiyi im. L.V. Pysarzheva'koho Akademiyi nauk Ukrayins'koyi RSR (for Vystos'-kyy and Neymark). (Sorbents)

VYSOTSKIY, Z. Z.

USSR/Chemistry - Adsorption

11 Sep 53

"The Influence of the Hydrophobic Component of Mixed Adsorbents on the Formation Mechanism of Their Porous Structure," Z. Z. Vysotskiy and I. Ye. Neymark, Inst of Phys Chem im L. V. Pisarzhevshiy, Acad Sci Ukr SSR.

DAN SSSR, Vol 92, No 2, pp 347-350 .

During the formation of adsorbents prep'd from carbon and silica gel, there is an increase in the apparent density of the silica gel as the amount of carbon is increased. This is due to penetration of silicic acid into the carbon. After passing a

269T19

max, the apparent density (corresponding to an increase of porosity) drops sharply as the amount of carbon is increased. This drop is due to the hydrophobic action of the carbon which prevents contraction of the SiO_2 in dehydration. Presented by Acad M. M. Dubinin 23 Jun 53.

VYSOTSKIY, Z.Z.; NEYMARK, I.Ye.; DUBININ, M.M., akademik.

Effect of the hydrophobic component of mixed sorbents, on the mechanism of formation of their porous structure. Dokl. AN SSSR 92 no.2:357-359 S '53.
(MIRA 6:9)

1. Akademiya nauk SSSR (for Dubinin). 2. Institut fizicheskoy khimii im. K.V.Pisarshevskogo Akademii nauk Ukrainakoy SSR (for Vysotskiy and Neymark).
(Sorbents)

VYSOTSKIY, Z.Z.; NEYMARK, I.Ye.

Structure and sorptive properties of mixed sorbents -- aluminosilica gels. Ukr.khim,zhur. 20 no.5:513-522 '54. (MLRA 8:1)

1. Institut fizicheskoy khimii im. L.V.Pisarzhevskogo Akademii nauk USSR.

(Sorbents) (Silica)

Vysotskiy, Z. Z.

USSR/Physical Chemistry - Kinetics. Combustion. Explosives. Topochemistry.
Catalysis, B-9

Abst Journal: Referat Zhur - Khimiya, No 1, 1957, 450

Author: Vysotskiy, Z. Z., and Polyakov, M. V.

Institution: None

Title: On the Effect of Small Additions of Nitric Oxides on the Oxidation
of Methane in the Presence of a Platinum Catalyst

Original
Periodical: Ukr. khim. zh., 1956, Vol 22, No 2, 180-185

Abstract: The oxidation of CH_4 by air in the presence of nitric oxides at 550° was studied with the aid of a differential thermocouple in a cylindrical reaction vessel coated with Pt; the reaction mixture contained 15% CH_4 . A preliminary flushing of the reactor with a mixture of nitric oxides and air increases the initial temperature rise (ΔT_{max}) and reduces the time required to attain it. At total pressures of 0-400 mm Hg, ΔT_{max} is proportional to the percent of nitric oxides present in the mixture (0.13-0.68%). When the pressure increases

Card 1/2

USSR/Physical Chemistry - Kinetics. Combustion. Explosives. Topochemistry.
Catalysis, B-9

Abst Journal: Referat Zhur - Khimiya, No 1, 1957, 450

Abstract: above 400 mm Hg, the ΔT_{\max} begins to fall off at 0.68% nitric oxide content in the mixture. At these pressures the ΔT_{\max} begins to decrease in the presence of nitric oxide. The authors are of the opinion that the nitric oxides, when present in small quantities, accelerate the homogeneous oxidation of the CH_4 by taking part in the primary heterogeneous step in which the chains are initiated at the Pt surface.

Card 2/2

VYSOTSKIY Z.Z.

USSR/Surface Phenomena. Adsorption. Chromatography. Ion Inter-
change

B-13

Abs Jour : Ref Zhur - Khimiya, No 8, 1957, 26364

Author : Z.Z. Vysotskiy, I.Ye. Neymark

Title : Special Case of Porous Structure of Mixed Sorbents in Sorption
Region

Orig Pub : Ukr. khim, zh., 1956, 22, No 4, 485-488

Abstract : The isotherms of sorption of C_6H_6 and H_2 vapors at 20° on coal (C) and silica gel (SG), and on carbon-silica gels (CSG) prepared on their basis were recorded by the method of quartz spring balance. The isotherms of C_6H_6 sorption on CSG differ sharply from isotherms on C and SG, especially by the presence of a vertical rise near $p/p_s = 1$. It is shown that this isotherm section is indicating the presence of macropores in CSG, in which capillary condensation of C_6H_6 takes place. The H_2O isotherms are also different on CSG-s and their components. The conclusions arrived at earlier (RZhKhim, 1954, 25053) regarding the part of C in the formation mechanism of the porous structure of CSG were confirmed.

Card : 1/1

VYSOTS, K. P., 2.2.

Y.M. 10:9
BALANDINA, V.A. [translator]; VYSOTSKIY, Z.Z. [translator]; BALANDIN, A.A.,
akademik, redaktor; RUBINSHTEYN, A.M., professor, redaktor; OGAND-
ZHANOVA, N.A., redaktor; BELEVA, M.A., tekhnicheskiiy redaktor

[Advances in catalysis and related subjects. Translated from the
English] Kataliz, issledovanie gomogennykh protsessov. Perevod s
angliiskogo V.A.Balandina i Z.Z.Vysotskogo. Pod red. A.A.Balandina,
A.M.Rubinshteina. Moskva, Izd-vo inostr.lit-ry, 1957. 252 p.
(Catalysis) (MLRA 10:9)

VYSOTSKIY, Z.Z. [Vysots'kiy, Z.Z.]; POLYAKOV, M.V.

Peculiarities of the oxidation of methane in the methane -
air mixture near its upper explosion limit [with summary in English].
Dop. AN URSS no.3:284-288 '58. (MIRA 11:5)

1. Institut fizichnoi khimii im. L.V. Pisarzhevskogo AN URSS.
Predstavleno akademikom AN URSS A.I. Brodskim [O.I. Broda'kim].
(Methane) (Oxidation)

VYSOTSKIY, Z. Z.

AUTHORS: Vysotskiy, Z.Z., and Shalya, V.V.

69-20-1-4/20

TITLE: The Heats of Hydration of Some Cations and the Effect of Their Adsorption on the Structure of Silica Gels (Teploty gidratatsii nekotorykh kationov i vliyaniye adsorbtsii poslednikh na strukturu silikagelya)

PERIODICAL: Kolloidnyy Zhurnal, 1959, Vol. XX, # 1, pp 29-33 (USSR)

ABSTRACT: The washing of silica gels, by solutions of various electrolytes, causes differences in the porous structure of the product. The principal cause is the pH of the medium, which influences the character of the ion exchange. In the article, the influence of the nature of some cations adsorbed by the hydrogel of silicic acid on the structure of the dry silica gel is investigated. The structural adsorption characteristics of the silica gels were determined by measuring the adsorption isotherms of methyl alcohol vapors, at 23°C, in a vacuum device with a quartz spring scale. Fig. 1 shows that the silica gel has a fine porous structure when the washing medium is strongly acid (pH 3.5). If the medium is weakly acid, neutral or alkaline, i.e. when a cation

Card 1/3

69-20-1-4/20

The Heats of Hydration of Some Cations and the Effect of Their Adsorption on the Structure of Silica Gels

exchange is possible during formation and drying of the gel and the cations of the metal substitute H^+ on the surface of the micelles of the silicic acid, the structure of the dry silica gels gains a coarser porosity. It is established that between the heat of hydration of the investigated cations and their influence on the porous structure of dry silica gels (especially on the radius of the pores and the specific surface area), a direct connection exists. The lower the hydration heat in the scale $H^+ > Ca^{2+} > Na^+ > K^+$, the coarser the porosity of the silica gel, the lower its surface. It has been suggested that the degree of wettability of the silicic acid hydrogel framework has an important effect on the porous structure of the silica gels.

There is 1 figure, 2 tables, and 18 references, 14 of which are Soviet, 3 English, and 1 German.

Card 2/3

69-20-1-4/20

The Heats of Hydration of Some Cations and the Effect of Their Adsorption
on the Structure of Silica Gels

ASSOCIATION: Institut fizicheskoy khimii AN UkrSSR imeni L.V. Pisarzhevs-
kogo, Kiyev (Institute of Physical Chemistry of the Ukrainian
AS imeni L.V. Pisarzhevskiy, Kiyev)

SUBMITTED: July 6, 1956

AVAILABLE: Library of Congress
Card 3/3

VYSOTSKIY, Z.Z.; POLYAKOV, M.V.

Study of methane oxidation, Ukr. khim. zhur. 24 no.1:46-54
'58.

(MIRA 11:4)

1. Institut fizicheskoy khimii im. L.V. Pisarshevskogo AN USSR.
(Oxidation) (Methane)

AUTHORS:

Vysotskiy, Z.Z. and Shalya, V.V.

SOV/80-59-1-5/44

TITLE:

Properties of Silica Gels Obtained by Drying Gels of Silicic Acid in Vacuum (Svoystva silikageley, poluchennykh s shkoy geley kremnevoy kisloty v vakuume)

PERIODICAL:

Zhurnal prikladnoy khimii, 1959, Nr 1, pp 35-39 (USSR)

ABSTRACT:

The authors describe the results of a comparative investigation of silica gels obtained from the hydrogels, alcogels and benzogels of the silicic acid. A method of drying the gels of the silicic acid in vacuum at a lowered temperature was developed in the course of this investigation, and it is also described in the article. The properties of silica gels obtained under various conditions are as follows:

1. The dehydration of hydrogels of the silicic acid yields fine-porous silica gels with the uniform porous structure. The structure of benzogels almost does not depend on the method of drying but essentially depends upon the conditions of water substitution by the benzene;
2. The substitution of the water of a hydrogel by the ethyl alcohol at room temperature almost does not change the porous structure of the dry gel; the substitution of water by the benzene, however, leads to a change in the structure;
3. The surface tension of the intermicellar liquid does not generally play any important role in the formation of the porous structure of the silica gels. Physico-chemical

Card 1/2

SOV/80-59-1-5/41

Properties of Silica Gels Obtained by Drying Gels of Silicic Acid in Vacuum

processes proceeding on the surface of the micellar skeleton of the silica acid gels are, apparently, of the primary importance for the porous structure of the silica gels. There are 2 graphs, 1 diagram, 1 table and 4 Soviet references.

SUBMITTED: December 26, 1956

Card 2/2

5(4)

SOV/21-59-1-18/26

AUTHORS: Polyakov, M.V., Vysotskiy, Z.Z., Shalya, V.V. and Gushchin, P.P.

TITLE: On the Existence of a Heterogeneous-Homogeneous Mechanism in Fluid Catalysis Conditions (K voprosu o nalichii geterogenno-gomogenogo mekhanizma v usloviyakh flyuidnogo kataliza)

PERIODICAL: Dopovidi Akademii nauk Ukrains'koi RSR, 1959, Nr 1, pp 67-71 (USSR)

ABSTRACT: The method of fluid catalysis is used (on the example of the reaction of conversion of methanol into formaldehyde in the presence of a copper-pumice catalyst) to clear up the macromechanism of gas reactions in conditions as close as possible to the conditions of the usual industrial catalytic processes. The results in the whole, and the analysis thereof, lead to the conclusion that the studied catalytic process in the

Card 1/2

SOV/21-59-1-18/26

On the Existence of a Heterogeneous-Homogeneous Mechanism in Fluid Catalysis Conditions.

boiling contact layer is a complex heterogereous-homogencus reaction with homogeneous stages proceeding not only beyond the fluid catalyst's layer, but inside the catalyst's layer, between its grains, as well. The observed facts do not fit into the picture of a purely heterogeneous catalytic process. There are 4 graphs and 8 references, 6 of which are Soviet, 1 Italian and 1 English.

ASSOCIATION: Institut fizicheskoy khimii im. L.V. Pisarzhevskogo, AN UkrSSR (Institute of Physical Chemistry imeni L.V. Pisarzhevskiy of the AS UkrSSR).

PRESENTED: July 28, 1958, by A.I. Brodskiy, Member of the ASUkrSSR

Card 2/2

5.1190,5.3300

75676

SOV/80-32-10-25/51

AUTHORS: Polyakov, M. V., Shalya, V. V., Vysotskiy, Z. Z.

TITLE: Investigation of the Catalytic Conversion of Methanol Into Formaldehyde in Fluidized Bed

PERIODICAL: Zhurnal prikladnoy khimii, 1959, Vol 32, Nr 10, pp 2275-2283 (USSR)

ABSTRACT: Copper catalyst suspended in gaseous stream was used in the subject study which was conducted in a wide range of methanol vapor to air ratio, including the explosive range. Pumice and quartz were used as catalyst carriers; the optimum amount of catalyst was 24 mg copper to 1 cm³ of carrier. The temperature corresponding to the maximum yield of formaldehyde was lower than in catalysis over stationary catalyst layer (540-580° against 700-750°). The content of methanol vapor in the gaseous mixture corresponding to the maximum yield of formaldehyde was 30%. In the range of explosive mixtures, the yield of formaldehyde dropped

Card 1/5

Investigation of the Catalytic Conversion of
Methanol Into Formaldehyde in Fluidized Bed

75676

SOV/80-32-10-25/51

sharply, and the yield of CO_2 , H_2 , and CO increased. As the methanol content approached the lower limit of explosive mixtures (7% methanol), the yield of formaldehyde increased again. In the range of 9 to 20% methanol content, a flame appeared in some instances over the fluidized catalyst bed; sometimes a quick flash or explosion occurred. When a catalyst of lower activity was used, the formaldehyde yield dropped sharply when the temperature reached $540-550^\circ$, and a flame appeared over the fluidized bed. The appearance of this flame showed the presence of a homogeneous reaction within the composite heterogeno-homogeneous catalytic process. This homogeneous reaction originated on the surface of the catalyst; under different conditions, when the walls of the reaction vessel over the fluidized bed are overheated, such reactions can also originate as wall reactions. The presence of homogeneous reactions between the catalyst granules was confirmed by empirical data, as discussed below.

Caro 2/5

Investigation of the Catalytic Conversion of
Methanol Into Formaldehyde in Fluidized Bed

75676

80V/80-32-10-25/51




Fig. 3. Yield of products in relation to CH_3OH content in the mixture at 520° ; (A) yield (in %) of HCHO (1), H_2 (2), CO (3), CO_2 (4), O_2 (5); (B) content of CH_3OH (in %).

Card 3/5

Investigation of the Catalytic Conversion of
Methanol Into Formaldehyde in Fluidized Bed

75676
SOV/80-32-10-25/51

The gradual change of the curves expressing the yield of the products in relation to temperature up to the moment of the appearance of the flame, indicated that the flame constituted a growth of primary homogeneous stages in the space between the catalyst granules. The yield of formaldehyde was lower in stationary than in fluidized catalyst, other conditions being equal; this was explainable by the decrease of the gaps between the catalyst grains in the stationary state which reduced the chances of homogeneous reactions taking place in these gaps. Further, the decrease of the yield of formaldehyde, H_2 , and the decrease of the total rate of conversion with the decreasing flow velocity of the gas mixture could be explained only by the contraction of the gaps between the catalyst grains. Porous (with pumice carrier) and nonporous (with quartz carrier) catalysts gave identical yields; this showed that only the outside catalyst layer participated in the catalysis, and this is an additional, indirect argument in favor

Card 4/5

Investigation of the Catalytic Conversion of
Methanol Into Formaldehyde in Fluidized Bed

75676

SOV/80-32-10-25/51

of the heterogeno-homogeneous mechanism of the catalytic process. The yield of formaldehyde was from 70 to 74% calculated on methanol; this was considerably higher than the yield over stationary catalyst layer; the above study is, therefore, of practical interest. There are 7 figures; 1 table; and 14 references, 2 U.S., 1 Belgian, 1 British, 10 Soviet. The U.S. references are: Nader, R. N., Wallace, R. D., McKinney, R. W., Ind. Eng. Chem., 44, 1508 (1952); Jones, E., Fowlie, G. G., J. Appl. Chem., 3, 206 (1953).

SUBMITTED: August 15, 1958

Card 5/5

5.1115

24068
S/069/61/023/003/001/004
B127/B217

AUTHORS: Vysotskiy, Z. Z., Divnich, L. F., Polyakov, M. V.

TITLE: Effect of vaporous shaping agents on porous structures and on the sorption properties of a silica gel surface

PERIODICAL: Kolloidnyy zhurnal, v. 23, no. 3, 1961, 248-254

TEXT: The paper deals with new experimental results for clarifying the mechanism in the microrelief formation and the sorption properties of the xero gel surface. Synthesis method: silica gel specimens were treated with benzene-, toluene-, orthoxylene-, dioxane-, isopropanol-, and methanol vapor. The sorption isotherms of toluene vapor were measured in these as well as in a corresponding check specimen at 20°C in vacuum by a quartz spring balance. The isotherms of benzene vapor were recorded in the same manner. The specific surface S of the specimens studied was determined by the BET method. A basal surface of 32 Å was assumed for one benzene molecule. The pore radius of silica gel is best determined by the desorption branch of the sorption isotherm of toluene. The adsorption isotherm of methyl orange for "benzene, toluene, xylene gels" was taken from

X

Card 1/4

21,068
S/069/61/023/003/001/004
B127/B217

Effect of vaporous shaping agents on...

a 5 % CH_3COOH solution. The size of all adsorption isotherms was referred to 1 m^2 gel surface. It was found that (a) the primary adsorption agrees with the desorption in the branch of the sorption isotherms of benzene vapor in the zone of small p/p_s for all specimens and that the corresponding branches of isotherms do not meet in the case of toluene adsorption. (b) More intensive adsorption of toluene as compared with benzene, in the reversible part of the isotherm. (c) The adsorption of methyl orange decreases in the order: gel treated with benzene > toluene > o-xylene. The first of these results is explained by an alteration of the mutual position of the mobile surface groups, e.g., of the hydroxyl groups, under the influence of the orienting effect of the adsorbed molecules. This effect is the greater, the more polar the adsorbed molecules are. A decrease of the H-bonds between adjacent surface molecules is assumed as fundamental process by which hydroxyls are liberated for their subsequent participation in the adsorption of molecules from the vapor phase. This also explains the initially inconsiderable adsorption. The increasing toluene covering of the gel, above all after its condensation in the gel pores, facilitates the liberation and the position change of surface hydroxyls. At the moment of occupation of all sorption spaces with toluene, this reorganization of

Card 2/4

24068

S/069/61/023/003/001/004

B127/B217

Effect of vaporous shaping agents on...

the gel surface is complete, and the desorption branch corresponds to an equilibrium state, also when p/p_s is small. This is also observed in the toluene adsorption isotherm. S increases in the case of polar molecules of toluene, orthoxylene, and isopropyl alcohol. Methanol and dioxane, the properties of which resemble more those of water than those of other used shaping agents, form gels with maximum S . The quantity S is directly connected with the size of the elementary particles, of which the xerogel skeleton is composed. The latter depends on the chemical character of the shaping agent. The experimental data show that a connection between the physical properties of the shaping agent or the intermicellar liquid and the final structure of the gel is impossible, but they confirm the chemical interaction between shaping agent and gel. An effect of the surface tension of the intermicellar liquid on the formation was not observed either. There are 5 figures, 1 table, and 15 references: 10 Soviet-bloc and 5 non-Soviet-bloc. The most important reference to the English-language publication reads as follows: R. G. Haldeman, P. H. Emmett, J. Phys. Chem. 59, 103, 1955.

ASSOCIATION: Institut fizicheskoy khimii AN USSR im. L. V. Pisarzhevskogo
(Institute of Physical Chemistry AS UkrESR imeni
L. V. Pisarzhevskiy)

Card 3/4

S/069/61/023/003/002/004
B127/B217

AUTHORS: Vysotskiy, Z. Z., Polyakov, M. V.

TITLE: Production of ultraporous silica gels of "intraparticular" porosity

PERIODICAL: Kolloidnyy zhurnal, v. 23, no. 3, 1961, 255-256

TEXT: The authors treat the production of anhydrous silica gel from aqueous silica gel at low temperatures. The gel thus produced adsorbs benzene and methanol to an inconsiderable extent, but large amounts of water. These sorption properties are explained by the fact that the porosity is preserved in the gel particles and its surface is chemically not affected. In the usual industrial methods, dehydration is carried out either at very high temperatures by evaporation or at very low temperatures by freezing. In either case, however, the basic structure of the hydrogel is destroyed. A new drying method was found in the course of the study of the effect of vapor pressure over the hydrogel, of temperature and dehydration rate on the silica gel structure. An intensive dehydration of the hydrogels of silicic acid under mild conditions occurs, while the gel

Card 1/3

Production of ultraporous silica gels of... S/069/61/023/003/002/004
B127/B217

structure is preserved. Aqueous silica gel is obtained by mixing sodium silicate solution and sulfuric acid. The washed gel was dried in the exsiccator with the aid of P_2O_5 , $CaCl_2$, alumina gel, silica gel, or concentrated sulfuric acid. In order to obtain a maximum reduction of the vapor pressure over the hydrogel, it was put into a Petri dish and the dish covered with a gauze net. Then, the dish was put in reverse position in the exsiccator, as closely as possible to the surface of the drying agent. In order to prevent the aging of the gel, the exsiccator was put in the refrigerator at approximately $0^\circ C$. 98-99 % of the water was evaporated by this method within 10-15 days, just as much as by six hours' heating in the drier at $180^\circ C$. After drying, the hydrogel was kept for 4-6 hr in the vacuum drying oven at $80-100^\circ C$. The adsorption isotherm of steam rises sharply at all p/p_s, and has a large hysteresis loop. The retardation of thermal gel aging in this method prevents the condensation to polysilicic acids under formation of siloxane bonds between the particles. As a result, an ultraporous xerogel was obtained in which the original porosity of the hydrogel was maintained. The table gives the sorption properties:

Card 2/3

Production of ultraporous silica gels of...

S/069/61/023/003/002/004
B127/B217

Type	Static activity, %	
	with C_6H_6	with H_2O
C-209 (S-209)	4.2	17.8
C-210 (S-210)	1.5	21.5
C-211 (S-211)	3.3	16.4
C-212 (S-212)	2.2	16.6

There are 1 figure and 1 table.

ASSOCIATION: Institut fizicheskoy khimii AN USSR im. L. V. Pisarzhevskogo
(Institute of Physical Chemistry AS UkrSSR imeni
L. V. Pisarzhevskiy)

SUBMITTED: May 24, 1960

Card 3/3

VYSOTSKIY, Z.Z.; DIVNICH, L.F.; POLYAKOV, M.V.

Effect of dissolved dyes on the formation of specific
adsorption properties of a silica gel surface. Dokl.
AN SSSR 139 no.6:1400-1402 Ag '61. (MIRA 14#8)

1. Institut fizicheskoy khimii im. L.V. Pizarzhevskogo
Akademii nauk USSR. Predstavleno akademikom A.A. Balandinym.
(Silica) (Adsorption)

VYSOTSKIY, Z.Z. [Vysots'kiy, Z.Z.]; DIVNICH, L.F.

Preparation, porous structure and sorptive characteristics of
specific absorbents - aluminosilicate gels. Dop. AN URSR no.4:
501-503 '62. (MIRA 15:5)

1. Institut fizicheskoy khimii AN USSR. Predstavleno akademikom
AN USSR A.I.Brodskim [Brods'kiy, O.I.].
(Aluminosilicates)

VYSOTSKIY, Z.Z.; DIVNICH, L.F.; BUTSKO, S.S.

Method for recording absorption spectra of dyes in transmitted
light on plate-shaped silica and aluminosilicate gels. Cpt.
1 spektr. 12 no.2:327-328 F '62. (MIRA 15:2)

(Dyes and dyeing)

(Silica)

(Aluminosilicates)

S/073/62/028/002/002/006
B101/B110

AUTHORS: Vysotskiy, Z. Z., Divnich, L. F., Strelko, V. V.

TITLE: Influence of the degree of preliminary dehydration of hydrogels and of water-vapor pressure in the drying process on the structure of forming silicic-acid xerogels

PERIODICAL: Ukrainskiy khimicheskiy zhurnal, v. 28, no. 2, 1962, 156-161

TEXT: The present investigation includes (1) the influence of preliminary dehydration of silicic-acid hydrogels on the rate of formation of their pore structure in benzene vapor; (2) the influence of water-vapor pressure, P_{H_2O} , on the structure of silicic-acid xerogels at room temperature and

below; and (3) the influence of aging on structure formation. Results: (a) Silica gel dried in air at room temperature possessed a low static adsorptive capacity (21.8%) for benzene. Hydrogels dehydrated by 80-90% possessed at higher adsorptive capacity (39-58%). Dehydration up to 96.7% does not affect their static activity. The influence of C_6H_6 manifests itself in widening pores and in an increasing specific sorption volume.

Card 1/3

S/073/62/028/002/002/006
B101/B110

Influence of the degree of ...

(b) The pore diameter and the sorption volume of the xerogel increase with an increase in P_{H_2O} , to which also a longer drying period corresponds.

When dried over P_2O_5 ($P_{H_2O} = 2 \cdot 10^{-5}$ mm Hg), xerogel washed in H_2O (pH ~ 8)

had a static activity of 60.7% for C_6H_6 after 26 days which increased to 71.8% with xerogel dried over dilute H_2SO_4 (specific gravity 1.22;

$P_{H_2O} = 13$ mm Hg) for 75 days. (c) Hydrogel samples kept in water for 31,

88, or 102 days showed a density of 1.052, 1.065, and 1.080 g/cm³, and a water content of 882, 832, and 824% by weight, respectively. Accordingly aging also takes place under water. (d) A new method of obtaining silica gels is to prevent aging by drying at a low temperature. Drying over silica gel, aluminogel, $CaCl_2$, and concentrated H_2SO_4 at 0°C or at room

temperature showed that the xerogels obtained at 0°C had almost completely lost their ability to adsorb benzene (1.5-4.2%), while they still adsorbed 16.4-21.5% of water vapor. This effect is attributed to the formation of ultrapores. There are 5 figures and 3 tables.

Card 2/3

Influence of the degree of ...

S/073/62/028/002/002/006
B101/B110

ASSOCIATION: Institut fizicheskoy khimii im. L. V. Pisarzhevskogo AN USSR
(Institute of Physical Chemistry imeni L. V. Pisarzhevskiy
AS UkrSSR)

SUBMITTED: May 24, 1960

Card 3/3

5.3833

40390
S/020/62/145/006/014/015
B106/B144

AUTHORS: Strelko, V. V., Ganyuk, L. N., Kachkurova, I. Ya, and
Vysotskiy, Z. Z.

TITLE: Polycondensation of acetaldehyde on dehydrating silica gel

PERIODICAL: Akademiya nauk SSSR. Doklady, v. 145, no. 6, 1962, 1297 - 1300

TEXT: Polycondensation occurred at room temperature when silica hydrogels liberated from salts with the aid of distilled or acidified (pH 4) water were desiccated by heating CaCl_2 in acetaldehyde vapor atmosphere, the silica gel being dissolved in 1 N NaOH to isolate the polycondensate. The polymer was extracted with benzene. It consists of partially oxidized polyene aldehydes with similar molecular weights, and is red-brown, viscous, and soluble in organic solvents. Further polycondensation and cross-linkage of the polymer molecules set in if silica gel and the polymer are kept for 2 hrs at 120°C and for 1 hr at 150°C in air. The product is dark-brown, insoluble in benzene and CCl_4 , and partially soluble in acetone. If the polymer obtained at room temperature after the separation

Card 1/3

S/020/62/145/006/014/015
B106/B144

Polycondensation of acetaldehyde on ...

of silica gel is heated, the conjugations of the C=C double bonds are destroyed by oxidation and diene-type synthesis. The polymer structures, and thereby the course of polycondensations, were confirmed by e.p.r. and IR absorption spectra. The e.p.r. signals show that the polyenes form a temperature-dependent reversible donor - acceptor complex with the silica gel surface, which is destroyed by heating and restored by cooling. Adsorption experiments with methanol and water vapors, performed on silica gel containing the polycondensate, showed that the polymer does not completely block the pores of silica gel. It is assumed that part of the polymer molecules are linked with the macroradicals $\equiv\text{Si-O}\cdot$ and $\equiv\text{Si}\cdot$ which form by a radical mechanism during the desiccation of the gel through rupture of the siloxane bonds between the micelles. Silica gels with similar properties also form from hydrogels desiccated in vinyl acetate vapors is hydrolyzed of vinyl acetate to acetic acid and acetaldehyde which decomposes to polyene aldehydes. Silica gels containing polymers with conjugated double bonds, are suitable for use as active fillers which simultaneously act as acceptors of free radicals. There are 3 figures. The most important English-language reference is: E. R. Blout, M. Fields, R. Karplus, J. Am. Chem. Soc., 70, 194 (1948).

Card 2/3

Polycondensation of acetaldehyde on ...

8/020/62/145/006/014/015
B106/B144

ASSOCIATION: Institut fizicheskoy khimii im. L. V. Pisarzhevskogo
Akademii nauk USSR (Institute of Physical Chemistry imeni
L. V. Pisarzhevskiy of the Academy of Sciences UkrSSR)

PRESENTED: May 5, 1962, by V. A. Kargin, Academician

SUBMITTED: May 4, 1962

Card 3/3

MITSYUK, B.M.; VYSOTSKIY, Z.Z.; POLYAKOV, M.V.

Role played by the polarity of the intramicellar liquid and by the intensity of its interaction with the surface of silicic acid hydrogel particles in the formation of silica gel texture. Dokl. AN SSSR 155 no.6:1404-1406 Ap '64. (MIRA 17:4)

1. Institut fizicheskoy khimii im. L.V.Pisarzhevskogo AN UkrSSR. Predstavleno akademikom P.A.Rebinderom.

STRELKO, V.V.; GUSHCHIN, P.P.; VYSOTSKIY, Z.Z.

Interaction of certain amino compounds with silica gels
subjected to dehydration. Dokl. AN SSSR 153 no.3:619-621
N '63. (MIRA 17:1)

1. Institut fizicheskoy khimii im. L.V. Pisarzhevskogo AN
SSSR. Predstavleno akademikom V.A. Karginym.

MITSYUK, B.M.; VYSOTSKIY, Z.Z.

Possibility of changing the texture of silicic acid xerogels in the process of vapor sorption. Dokl. AN SSSR 152 no.5:1166-1168 (MIRA 16:12)
O '63.

1. Institut fizicheskoy khimii im. L.V.Pisarzhevskogo AN UkrSSR.
Predstavleno akademikom M.M.Dubininym.

STRELKO, V.V.; GANYUK, L.N.; VISOTSKIY, Z.Z.

Appearance of paramagnetism during adsorption of anthracene
by dehydrated aluminosilicate, silica gel, and alumina gel.
Ukr. khim. zhur. 29 no.4:363-365 '63. (MIRA 16:6)

1. Institut fizicheskoy khimii im. L.V. Pissarzhevskogo AN
UkrSSR.

(Anthracene) (Adsorption)
(Electron paramagnetic resonance and relaxation)

VYSOTSKIY, Z.Z.; DIVNICH, L.F.

Formation of a porous structure of chalklike aluminum hydroxide
gels in the vapors of the conditioning agents. Ukr.khim.zhur. 29
no.1:64-66 '63. (MIRA 16:5)

1. Institut fizicheskoy khimii im. L.V.Pisarshevskogo AN UkrSSR.
(Aluminum hydroxide) (Porosity)

POLISHCHUK, Yu.N.; KORNIYENKO, T.P.; VYSOTSKIY, Z.Z.

Polymerization of styrene, vinyl acetate, and methyl methacrylate in the presence of aluminosilica gel coatings. Ukr.khim.zhur. 29 no.3:325-329 '63. (MIRA 16:4)

1. Institut fizicheskoy khimii imeni L.V.Pisarzhevskogo.
(Polymerization) (Organic compounds) (Aluminosilicates)

GRAGEROV, I. P.; PONOMARCHUK, M. P.; STRELKO, V. V.; GANYUK, L. N.;
VYSOTSKIY, Z. Z.

Free radical formation in benzoquinhydrone and phenazohydrin
on solid surfaces studied by the electron paramagnetic
resonance method. Dokl. AN SSSR 147 no.4:867-869 D '62.
(MIRA 16:1)

1. Institut fizicheskoy khimii im. L. V. Pisarzhevskogo AN
UkrSSR. Predstavleno akademikom M. I. Kabachnikom.

(Quinhydrone) (Phenazine) (Radicals(Chemistry))

SKARCHENKO, Vladimir Konstantinovich; VYSOTSKIY, Z.Z., otv. red.;
POKROVSKAYA, Z.S., red.; TURVANOV, N.A., tekhn. red.

[Aluminosilicate catalysts in the light of the modern
theory of heterogeneous catalytic processes] Aliumosili-
katnye katalizatory v svete sovremennoi teorii getero-
genno-kataliticheskikh protsessov. Kiev, Izd-vo Akad.
nauk USSR, 1963. 117 p. (MIRA 16:4)
(Aluminosilicates) (Catalysis)

S/073/63/029/003/006/003
A057/A126

AUTHORS: Polishchuk, Yu. N., Korniyenko, T. P., Vysotskiy, Z. Z.

TITLE: Polymerization of styrene, vinylacetate, and methyl methacrylate in the presence of alumo-silica gel coatings

PERIODICAL: Ukrainskiy khimicheskiy zhurnal, v. 29, no. 3, 1963, 325 -329

TEXT: Polymerization kinetics of the radical polymerization in liquid phase were studied with styrene, vinylacetate, and methyl methacrylate in reaction vessels with alumo-silica gel coatings. Also investigated was the effect of xerogels, formed in vapors of the investigated monomer, and the structure-adsorptive and catalytic properties were compared with control samples. The present work was carried out in the Institut fizicheskoy khimii im. L. V. Pisarzhevskogo (Institute of Physical Chemistry imeni L. V. Pisarzhevskiy) in continuation of earlier investigations (Ukr.khim.zhur., v. 28, 1962, 1024) with non-porous coatings. The hydrogel was prepared in the usual manner forming alumosilic acid. Thus the alumo-silica gel surface showed properties of a strong acid. The process with monomer vapors resulted after drying in a yellow-

Card 1/3

S/073/63/029/003/006/009
A057/A126

Polymerization of styrene,...

brown product in case of styrene, in a black product with vinylacetate, and in a colourless product with methyl methacrylate. Adsorption isotherms of methanol vapors on the alumo-silica gel samples treated with styrene or vinylacetate show two characteristics: both curves lie below the control curve and have reproducible hysteresis loops. This is explained by the change of the xerogel surface effected by grafting of polymer chains to it. Thus, a polystyrene skeleton is formed in the pores of the gel. The adsorption isotherm of the methyl methacrylate alumo-silica gel lies above the control sample curve. This difference to the other two samples is in agreement with the colour difference observed, showing thus a connection between the two effects. The prepared alumo-silica gels were applied, powdered ($100 - 250 \mu$) and mixed with water glass, to the inner surface of the reaction vessel. The polymerization was carried out with 1% benzoyl peroxide admixture in nitrogen atmosphere. The technique used was described in an earlier paper (Zh. fiz. khim., v. 25, 1951, 647). A strong effect of the drying method of the alumo-silica gel on styrene and vinyl acetate polymerization kinetics was observed. This effect was especially pronounced for alumo-silica gel coatings dried over CaCl_2 in the monomer vapor. The styrene polymerization is initiated at 85°C , that of vinyl acetate above 65°C .

Card 2/3

S/073/63/023/003/006/009
A057/A126

Polymerization of styrene...

No effect could be observed in methyl methacrylate polymerization, except a shortening of the induction period. The obtained results prove the assumption of the heterogeneous-homogeneous mechanism of the process studied. However, the expected specific polymerization of the monomer effected by the alumo-silica gel was not observed. This effect is apparently restrained by the change of the chemical nature of the surface because of the intensive polymerization occurring on the alumo-silica gel surface. There are 4 figures.

ASSOCIATION: Institut fizicheskoy khimii im. L. V. Pisarzhevskogo (Institute of Physical Chemistry im. L. V. Pisarzhevskiy)

SUBMITTED: January 4, 1962
Card 3/3

VYSOVSKIKH, Ivan Petrovich; AKILOV, G.P., red.; LUK'YANOV, A.A.,
tekh. red.

[Lectures on calculation methods] Lektsii po metodam vychislenii.
Moskva, Fizmatgiz, 1962. 342 p. (MIRA 15:7)
(Calculus)

VYSOVSKIY, D.M.

USSR / Radio Physics. Propagation of Radio Waves.

I-6

Abs Jour : Ref Zhur - Fizika No 3, 1957, No 7325

Author : Vysovskiy, D.M.

Title : Certain Features of Calculation of Radio Refraction

Orig Pub : Radiotekhnika i elektronika, 1956, 1, No 3, 274-276

Abstract : The author considers expressions for the angle of radio refraction α in the form of an integral and a series. It is shown that the integral expression for the angle of radio refraction can be represented in the form of an alternating series in odd powers of $\tan z$, where z is the visible zenith angle; for small z the series converges very rapidly. If α is determined with an accuracy to 1" it is enough to use the first term of the series for $z < 70^\circ$, two terms for $z < 82^\circ$, and three terms for $z < 85 - 86^\circ$. It is indicated that if the accuracy is 1' this series can be used only for $z < 87 - 88^\circ$. At greater values of z , the series becomes divergent. It is noted that the multiplier of the

Card : 1/2

- 45 -

USSR / Radio Physics. Propagation of Radio Waves.

I-6

Abs Jour : Ref Zhur - Fizika No 3, 1957, No 7325

Abstract : first principal term of the series depends only on the value of the index of refraction at the earth's surface. Therefore, in the cases when it is possible to use only the first term of the series in the calculations, the Laplace theorem, known from the theory of astronomical refraction, becomes valid, and the radio refraction does not depend on the distribution of the index of refraction with altitude.

Card : 2/2

- 46 -

COMMON ELEMENTS										PROCESSES AND PROPERTIES INDEX										100 AND 170 (RUBIN)									
COMMON ELEMENTS										PROCESSES AND PROPERTIES INDEX										100 AND 170 (RUBIN)									
<p>CH</p>																													
<p>Portable gas producer. D. I. Vysotskii, Russ. 51,654, Aug. 31, 1938. Construction details.</p>																													
<p>ASB-51A METALLURGICAL LITERATURE CLASSIFICATION</p>										<p>100 AND 170 (RUBIN)</p>										<p>100 AND 170 (RUBIN)</p>									
<p>100 AND 170 (RUBIN)</p>										<p>100 AND 170 (RUBIN)</p>										<p>100 AND 170 (RUBIN)</p>									

Effect of the concentration of salts in the water on the quality of the clay suspension (used in drilling). 1. Vymetali. *Nefteyane* 19, No. 10, 8 (1938); *Chemie de industrie* 41, 1985. The concn. of salts in the water used in drilling for prepn. of clay suspension should correspond to about 10 g/l, which ensures stability and optimum filtering power of the suspension. On the other hand, suspensions prepd. with fresh water give rise to lixiviation of the sedimentary layers, and the salt content of the suspension gradually builds up; but this lixiviation disintegrates the sedimentary layers and can produce landslides. A. Papineau-Couture

New South Emba crude oils. I. V. Vysotskiy. *Vostochnaya Neft* 1939, No. 2, 17-21. The new crude oils are of four types: (1) Heavy, highly resinous, nonparaffinic, low-S, naphtha-free oils of Neomurian age, that are found in the Tyukchen and Kul-Sary deposits (well 4). This type is similar to that produced from the Neomurian basins of Kochagyl. (2) Heavy, resinous, nonparaffinic naphtha-free, low-S crude oils from Bagla (well 3) and Tas-Kudak. The distillate oils have a medium sp. gr. and a low pour pt. (3) Light, resinous, paraffinic, S-free crude oils from eastern Bakhunas and southern Kochagyl. The crude oil from Bakhunas does not contain gasoline or naphtha, while that from Kochagyl contains 15.5% of naphtha. The lubricating oil fractions have a low sp. gr. and high pour pt. To this group may also be added the nonparaffinic northern Iskin crude oil. The stripped crude oil is a good raw material for the prepn. of special light machine oil fractions. The residue constitutes a bitumen. (4) Light, slightly resinous, slightly paraffinic Bagla (well 20) crude oil with a medium content of gasoline and naphtha fractions of Aptian age. The distillates have a low sp. gr. and a high pour pt. This oil can be refined together with the Permian-Mesozoic Makat crude oil. Detailed analytical data are tabulated. A. A. B.


ASB-51A METALLURGICAL LITERATURE CLASSIFICATION

FROM STAINLESS

FROM STAINLESS

Crude oil from the Kulsary deposit. J. V. Vysotskii, *Nefteyané Khos.* 1939, No. 6, 40 v. This paraffinic oil contains fractions boiling below 100, 130, 140, 180, 200, 280, 300 and 300°, resp., of 16.4, 20.2, 32.8, 30.6, 39.3, 44.3, 48.8 and 08.9%. It is low in resins. The straight-run gasoline has a low octane no. The kerosene fraction runs clear. The fuel-oil (stripped crude) fraction amounts to 28%, and high-grade lubricating oils can be prep'd. from the bottoms. A. A. B.

ASB-51 METALLURGICAL LITERATURE CLASSIFICATION



1ST AND 2ND CATEGORIES													3RD AND 4TH CATEGORIES												
PROCEDURES AND PROPERTIES INDEX																									
<p><i>ca</i></p> <p>The Archedin gas deposit. V. G. Vasil'ev, L. V. Kyslovskiy, and F. M. Pantel'ev. <i>Neftyanoe Khoz.</i> 23, No 6, 17-23 (1971). - Stratigraphic features of the gas-bearing structure discovered 150 km. northwest of Stalingrad are described. Bruno C. Metzner</p>																									
<p>ASB-11A DETALLURGICAL LITERATURE CLASSIFICATION</p>																									
130000 00													130000 00												
130000 00													130000 00												

1ST AND 2ND DODGES										3RD AND 4TH DODGES									
PROCESSING AND PROPERTIES INDEX																			
ca										20									
<p>Artificial marble. P. Vysotskii. <i>Novosti Tekhniki</i> 1937, No. 15, 35-6. - A raw dolomite is burned at 650-700° (CaO content should be below 2.5%), powdered (1600 mesh per sq. cm.), and mixed with a $MgCl_2 \cdot 6H_2O$ soln. (22°Bé.) at a ratio of 550 cc. of soln. per kg. of dolomite powder, for not less than 5 min. After addn. of coloring matter, the mixt. is left in molds at 25-30° for 24 hrs., then for 2 days at the same temp. but without forms, and finally at 70° to const. wt. The glossy side of the artificial marble is then covered with a mixt. of white wax 1, paraffin 1, turpentine 2 and kerosene 20 parts, and dried for 2-3 days at normal temp. A. A. Podgorniy</p>																			
ASM-A6 METALLURGICAL LITERATURE CLASSIFICATION																			
12000 12100 12200										12300 12400 12500									
12600 12700 12800										12900 13000 13100									
13200 13300 13400										13500 13600 13700									
13800 13900 14000										14100 14200 14300									
14400 14500 14600										14700 14800 14900									
15000 15100 15200										15300 15400 15500									
15600 15700 15800										15900 16000 16100									
16200 16300 16400										16500 16600 16700									
16800 16900 17000										17100 17200 17300									
17400 17500 17600										17700 17800 17900									
18000 18100 18200										18300 18400 18500									
18600 18700 18800										18900 19000 19100									
19200 19300 19400										19500 19600 19700									
19800 19900 20000										20100 20200 20300									
20400 20500 20600										20700 20800 20900									
21000 21100 21200										21300 21400 21500									
21600 21700 21800										21900 22000 22100									
22200 22300 22400										22500 22600 22700									
22800 22900 23000										23100 23200 23300									
23400 23500 23600										23700 23800 23900									
24000 24100 24200										24300 24400 24500									
24600 24700 24800										24900 25000 25100									
25200 25300 25400										25500 25600 25700									
25800 25900 26000										26100 26200 26300									
26400 26500 26600										26700 26800 26900									
27000 27100 27200										27300 27400 27500									
27600 27700 27800										27900 28000 28100									
28200 28300 28400										28500 28600 28700									
28800 28900 29000										29100 29200 29300									
29400 29500 29600										29700 29800 29900									
30000 30100 30200										30300 30400 30500									
30600 30700 30800										30900 31000 31100									
31200 31300 31400										31500 31600 31700									
31800 31900 32000										32100 32200 32300									
32400 32500 32600										32700 32800 32900									
33000 33100 33200										33300 33400 33500									
33600 33700 33800										33900 34000 34100									
34200 34300 34400										34500 34600 34700									
34800 34900 35000										35100 35200 35300									
35400 35500 35600										35700 35800 35900									
36000 36100 36200										36300 36400 36500									
36600 36700 36800										36900 37000 37100									
37200 37300 37400										37500 37600 37700									
37800 37900 38000										38100 38200 38300									
38400 38500 38600										38700 38800 38900									
39000 39100 39200										39300 39400 39500									
39600 39700 39800										39900 40000 40100									
40200 40300 40400										40500 40600 40700									
40800 40900 41000										41100 41200 41300									
41400 41500 41600										41700 41800 41900									
42000 42100 42200										42300 42400 42500									
42600 42700 42800										42900 43000 43100									
43200 43300 43400										43500 43600 43700									
43800 43900 44000										44100 44200 44300									
44400 44500 44600										44700 44800 44900									
45000 45100 45200										45300 45400 45500									
45600 45700 45800										45900 46000 46100									
46200 46300 46400										46500 46600 46700									
46800 46900 47000										47100 47200 47300									
47400 47500 47600										47700 47800 47900									
48000 48100 48200										48300 48400 48500									
48600 48700 48800										48900 49000 49100									
49200 49300 49400										49500 49600 49700									
49800 49900 50000										50100 50200 50300									
50400 50500 50600										50700 50800 50900									
51000 51100 51200										51300 51400 51500									
51600 51700 51800										51900 52000 52100									
52200 52300 52400										52500 52600 52700									
52800 52900 53000										53100 53200 53300									
53400 53500 53600										53700 53800 53900									
54000 54100 54200										54300 54400 54500									
54600 54700 54800										54900 55000 55100									
55200 55300 55400										55500 55600 55700									
55800 55900 56000										56100 56200 56300									
56400 56500 56600										56700 56800 56900									
57000 57100 57200										57300 57400 57500									
57600 57700 57800										57900 58000 58100									
58200 58300 58400										58500 58600 58700									
58800 58900 59000										59100 59200 59300									
59400 59500 59600										59700 59800 59900									
60000 60100 60200										60300 60400 60500									
60600 60700 60800										60900 61000 61100									
61200 61300 61400										61500 61600 61700									
61800 61900 62000										62100 62200 62300									
62400 62500 62600										62700 62800 62900									
63000 63100 63200										63300 63400 63500									
63600 63700 63800										63900 64000 64100									
64200 64300 64400										64500 64600 64700									
64800 64900 65000										65100 65200 65300									
65400 65500 65600										65700 65800 65900									
66000 66100 66200										66300 66400 66500									
66600 66700 66800										66900 67000 67100									
67200 67300 67400										67500 67600 67700									
67800 67900 68000										68100 68200 68300									
68400 68500 68600										68700 68800 68900									
69000 69100 69200										69300 69400 69500									
69600 69700 69800										69900 70000 70100									
70200 70300 70400										70500 70600 70700									
70800 70900 71000										71100 71200 71300									
71400 71500 71600										71700 71800 71900									
72000 72100 72200										72300 72400 72500									
72600 72700 72800										72900 73000 73100									
73200 73300 73400										73500 73600 73700									
73800 73900 74000										74100 74200 74300									
74400 74500 74600										74700 74800 74900									
75000 75100 75200										75300 75400 75500									
75600 75700 75800										75900 76000 76100									
76200 76300 76400										76500 76600 76700									
76800 76900 77000										77100 77200 77300									
77400 77500 77600										77700 77800 77900									
78000 78100 78200										78300 78400 78500									
78600 78700 78800										78900 79000 79100									
79200 79300 79400										79500 79600 79700									
79800 79900 80000										80100 80200 80300									
80400 80500 80600										80700 80800 80900									
81000 81100 81200										81300 81400 81500									
81600 81700 81800										81900 82000 82100									
82200 82300 82400										82500 82600 82700									
82800 82900 83000										83100 83200 83300									
83400 83500 83600										83700 83800 83900									
84000 84100 84200										84300 84400 84500									
84600 84700 84800										84900 85000 85100									
85200 85300 85400										85500 85600 85700									
85800 85900 86000										86100 86200 86300									
86400 86500 86600										86700 86800 86900									
87000 87100 87200										87300 87400 87500									
87600 87700 87800										87900 88000 88100									
88200 88300 88400										88500 88600 88700									
88800 88900 89000										89100 89200 89300									
89400 89500 89600										89700 89800 89900									
90000 90100 90200										90300 90400 90500									
90600 90700 90800										90900 91000 91100									
91200 91300 91400										91500 91600 91700									
91800 91900 92000										92100 92200 92300									
92400 92500 92600										92700 92800 92900									
93000 93100 93200										93300 93400 93500									
93600 93700 93800										93900 94000 94100									
94200 94300 94400										94500 94600 94700									
94800 94900 95000										95100 95200 95300									
95400 95500 95600										95700 95800 95900									
96000 96100 96200										96300 96400 96500									
96600 96700 96800										96900 97000 97100									
97200 97300 97400										97500 97600 97700									
97800 97900 98000										98100 98200 98300									
98400 98500 98600										98700 98800 98900									
99000 99100 99200										99300 99400 99500									
99600 99700 99800										99900 100000 100100									

137 AND 138 COPIES										139 AND 140 COPIES									
PROCESSES AND PROPERTIES INDEX																			
<div style="text-align: right;">20</div> <div style="text-align: left;">CA</div> <p>Raw materials for the production of white portland cement. P. G. Vysotskiy. <i>Prum. Stroi. Material</i>, 2, No. 12, 8-10(1960). Characteristics are given of clays and limestones suitable for the production of white portland cement in the mid-Volga region. B. R. Stefanovsky</p>																			
ASB-31A METALLURGICAL LITERATURE CLASSIFICATION																			
FROM SYNOPTIC										FROM SYNOPTIC									
140000 141000 142000 143000 144000 145000 146000 147000 148000 149000										150000 151000 152000 153000 154000 155000 156000 157000 158000 159000									
160000 161000 162000 163000 164000 165000 166000 167000 168000 169000										170000 171000 172000 173000 174000 175000 176000 177000 178000 179000									
180000 181000 182000 183000 184000 185000 186000 187000 188000 189000										190000 191000 192000 193000 194000 195000 196000 197000 198000 199000									

Raw material for white Portland cement. P. 8.
Vysshii Prom. Stroitel. Materialy, 1960, No. 12.
pp. 8-10. Khim. Referat. Zhur, 4 [6] 97-98 (1961). - V.

describes experiments in producing a white Portland cement from Kamachikhinsk and Chok clays and Shiryayev lime. If the conditions in the furnace were oxidizing, the clinker was yellow. In a reducing atmosphere, the clinker was light green. The addition of $K_2Cr_2O_7$ imparted a permanent green color to the cement. M. Ho.

VYSTARKIN, B. V., GANTCH, A.A.

30305

1 Eydyel' nant, L.I. Duti polnoy nyekhanizatsii pyeryerabotki gruzov na novykh myetall-urgichyeskikh zavodakh. Myekhanizatsiya trudoyemkikh 1 Tyazhyelykg rabot, 1949, No 9, s. 7-12

7. Tyekhnologiya Myetallov

SO: LETOPIS' No. 34

VYSTAVKIN, A

YUSHKIN, N.; NOVIKOV, M.; VYSTAVKIN, A.; KOTYUZHINSKIY, G.

Shortened workday and new wage terms in ferrous metallurgy. Sots.
trud no.12:103-118 D '57. (MIRA 11:1)

1. Nachal'nik otdela organizatsii truda stalingradskogo metallurgi-
chenkogo zavoda "Krasnyy Oktyabr'" (for Yushkin). 2. Nachal'nik
otdela organizatsii truda Nizhne-Tagil'skogo metallurgicheskogo
kombinata (for Novikov). 3. Nachal'nik otdela truda i zarobotnoy
platy moskovskogo zavoda "Serp i molot" (for Vystavkin). 4. Zame-
stitel' nachal'nika otdela truda i zarobotnoy platy Upravleniya
chernoy metallurgii Chelyabinskogo sovnarkhoza (for Kotyuzhinskiy).
(Steel industry)

LIFSHITS, T.M.; KOGAN, Sh.M.; VYSTAVKIN, A.N.; MEL'NIK, P.G.

Some phenomena induced in n-type indium antimonide by radio-frequency radiation. Zhur.eksp.i teor.fiz. 42 no.4:959-966 Ap '62.
(MIRA 15:11)

1. Institut radiotekhniki i elektroniki AN SSSR.
(Radio waves) (Indium-antimony alloys)

BERLIN, A.S.; VIZEL', A.A.; VISTAYKIN, A.N.; POPOV, Ye.I.; KNOTUNTSEV, Yu.L.;
SHTYKOV, V.D.

Parametric amplification in the 8 mm. band. Radiotekh. i elektron.
10 no.10:1907-1909 0 '65. (MIRA 18:10)

VYSTAVKIN, A. N. and LOMIZE, L. G. and BERNASHEVSKIY, G. A.

"Radiation of Relativistic Electron Flow at Millimeter Waves,"

report presented (by Bernashevskiy) at the 9th Symposium on Millimeter Waves,
31 Mar - 2 April 1959, Brooklyn Polytech. Inst, New York.

Inst. for Radioelectricity and Electronics, USSR

VYSTAVKIN, A. N.

11 июня
(с 18 до 22 часов)

Г. М. Рогов
Влияние магнитного электрического поля на
различные электрические процессы.
С. Г. Афонин
Об управлении частотой гравитационной
А. В. Чума
Изменения в спектре электрических
М. С. Арсенов
Метод получения магнитных волн отсюда на
различные частоты в магнитном поле
электрических волн.

12 июня
(с 10 до 16 часов)

В. В. Бугаев
В. В. Бугаев
В. В. Бугаев
Влияние магнитного поля на электрические
волны.

Г. А. Лобов
Изменения в спектре электрических
волн.

А. В. Бугаев
В. В. Бугаев
С. С. Бугаев
Влияние магнитного поля на электрические
волны.
А. В. Бугаев
В. В. Бугаев
В. В. Бугаев
В. В. Бугаев

Изменения в спектре электрических
волн.

В. В. Бугаев
Изменения в спектре электрических
волн.

13 июня
(с 10 до 16 часов)

А. В. Бугаев
Изменения в спектре электрических
волн.

report submitted for the Centennial Meeting of the Scientific Technological Society of
Radio Engineering and Electrical Communications in A. S. Popov (VSEKH), Moscow,
8-12 June, 1959

SOV/109- - 4-3-35/38

AUTHORS: Vystavkin, A.N., Anisimova, Yu.V., and Shakhidzhakov, S.S.

TITLE: Simulation of the Trajectories of Relativistic Electrons in a Magnetic Ondulator (Modelirovaniye trayektoriy relyativistskikh elektronov v magnitnom ondulyatore)

PERIODICAL: Radiotekhnika i Elektronika, Vol 4, Nr 3, 1959, pp 550-551 (USSR)

ABSTRACT: The equation of motion of an electron in a magnetic field can be written as:

$$\frac{dp}{dt} = e [\vec{v} \times \vec{H}] , \quad (1)$$

where p , e and v are the impulse, the charge and the velocity of an electron, while H is the magnetic field. If the radiation energy of the electron is neglected, Eq (1) can be written as Eq (2), where m_0 is the rest mass of an electron, while β is the ratio of the absolute velocity of the electron to the velocity of light. Eq (2) can also be written as Eq (3) where ds is an element of the curvi-linear trajectory of an electron. The vector of the curvature of the trajectory can be expressed by Eq (4). For the case of a non-relativistic electron, Eq (4) is in the form of Eq (5). By comparing

Card 1/3

SOV/109-- -4-3-35/38

Simulation of the Trajectories of Relativistic Electrons in a
Magnetic Ondulator

Eqs (4) and (5), it can be seen that, provided the initial co-ordinates and angles and the magnetic fields are identical, the two equations are also identical; the condition expressed by Eq (6) should also be fulfilled. The above result can be used to simulate the trajectories of relativistic electrons by means of a magnetic undulator such, for example, as described by H. Motz (Ref 1). The authors also devised an undulator and this is schematically illustrated in Fig 1. The device consists of: (1) an electron gun, (2) a mechanism for displacing the gun, (3) a bellows, (4) magnetic rails, (5) a drift tube with hermetically sealed windows, (6) a stationary collector electrode, (7) a device for imparting a motion in vacuum and (8) pole-pieces for producing the magnetic field. The authors make

Card 2/3

SOV/109- -4-3-35/38

Simulation of the Trajectories of Relativistic Electrons in a
Magnetic Ondulator

acknowledgement to G.A. Bernashevsky for suggesting the
problem and directing the work.
There are 3 figures and 1 English reference.

SUBMITTED: July 12, 1958

Card 3/3

66712

SOV/109-4-8-33/35

9.1300

AUTHORS: Vystavkin, A.N. and Shakhidzhanov, S.S.

TITLE: Excitation of the Waveguide of a Magnetic Ondulator
by an Extended Modulated Electron Beam of Finite Length

PERIODICAL: Radiotekhnika i elektronika, 1959, Vol 4, Nr 8,
pp 1404 - 1408 (USSR)

ABSTRACT: The problem of main interest in the analysis of a magnetic ondulator is the excitation of the waveguide by a train of relativistic electron bunches which move along a periodic trajectory of finite length. The problem can be solved approximately if the radiation losses and the reaction of the radiated field on the relativistic electron beam are neglected. Only the first harmonic of the periodic electron trajectory is considered. The current of the electron bunches moving along a sinusoidal trajectory (see Figure a) can be written in the form of Eqs (1) and (2), where \bar{v} is the velocity of the electrons along the axis z , v is the velocity of the electrons along the trajectory and j_{ω} is the amplitude of the current density at a

Card 1/4

66712

SOV/109-4-8-33/35

Excitation of the Waveguide of a Magnetic Ondulator by an Extended Modulated Electron Beam of Finite Length

frequency ω . The current component $j_{\omega y}$ can be represented by Eq (3), where the quantities γ are defined by Eqs (4). The radiation power for the s -th wave can be determined from Eq (5), where p_s is the power carried by the wave having an electric field component E_s (Ref 10). For a fine beam, Eq (5) can be written as Eq (6), where γ_s is the wave number of the s -th wave and L is the length of the waveguide section occupied by the radiating beam; i is the amplitude of one of the current components. From Eq (6), it is seen that a resonance is attained when:

$$\gamma_T = \gamma_s \quad (7) .$$

Consequently, the resonance frequencies for a uniform waveguide are given by Eqs (8), provided the waveguide is excited by a fast transverse wave of the type given

Card 2/4

66712

SOV/109-4-8-33/35

Excitation of the Waveguide of a Magnetic Ondulator by an Extended Modulated Electron Beam of Finite Length

by Eq (3). The radiation power in a rectangular waveguide of the ondulator for the H_{10} -wave is given by

Eq (10), provided the beam is concentrated near the axis of the waveguide. On the other hand, the radiation power of the E_{11} -wave is given by Eq (11). From the above

analysis, it is possible to draw the following conclusions:

- 1) the harmonics of the beam propagating in the waveguide of an ondulator of finite length are radiated when the beam is modulated;
- 2) it is possible to limit the number of the waves at which the resonance radiation occurs;
- 3) on the basis of Eq (10), it is possible to evaluate the optimum parameters for the ondulator so that a maximum radiation power will be obtained, and
- 4) the intensity of the radiation in the ondulator, in the presence of longitudinal currents, can be higher than that in the presence of transverse currents even in the absence of synchronism.

Card 3/4

4

66712

SOV/109-4-8-33/35

Excitation of the Waveguide of a Magnetic Ondulator by an Extended
Modulated Electron Beam of Finite Length

The authors express their gratitude to N.D. Devyatkov
and G.A. Bernashevskiy for valuable advice and for
directing this work.

There are 1 figure and 13 references, of which 6 are
English, 2 French and 5 Soviet.

SUBMITTED: January 20, 1959

Card 4/4

20567

S/109/60/005/06/012/021
E140/E163

9.1200

AUTHORS: Anisimova, Yu.V., Bernashevskiy, G.A.,
Vystavkin, A.N., and Lomize, L.G.

TITLE: Millimeter-Band Investigation of Waveguide Radiators
Excited by Relativistic Electron Streams

PERIODICAL: Radiotekhnika i elektronika, 1960, Vol 5, Nr 6,
pp 969-980 (USSR)

ABSTRACT: In previous theoretical and experimental studies in this field relativistic beams were used, accelerated and bunched in linear electron accelerators or accelerating resonators, fed by power resonators or accelerating waveband. Magnetic undulators and resonators operating at higher oscillation modes have been used, including dielectric-filled. The radiation power obtained experimentally was as a rule 10 to 100 mW in the longwave portion of the millimeter band but reduced to units or tenths of microwatts at waves of the order of 2 to 3 mm, apparently as a result of insufficiently good bunching of the beam. Cherenkov-radiation experiments were carried out only for low-voltage beams (of the order of 10 kV). The radiation power obtained was a fraction of

Card
1/5

8057

S/109/60/005/06/012/021
E140/E163

Millimeter-Band Investigation of Waveguide Radiators Excited by
Relativistic Electron Streams

a microwatt at a frequency of 24 Gcs, coinciding with the bunching frequency of the beam. In general Cherenkov radiation in the millimeter region has not been studied experimentally and the theoretical calculations have been carried out for single electrons moving in an unbounded space or an infinitely long waveguide and for an extended electron beam in an unbounded dielectric medium. Such different approaches to the problem make comparison difficult. In the present work different waveguide radiators are studied from a common point of view and an attempt is made to narrow the existing gap between theoretical and experimental results. The present article considers the following three types of waveguide radiators: smooth waveguide of finite length with rectilinear electron beam, dielectric field waveguide (Cherenkov radiator), magnetic undulator. The approach is to consider the radiation resistance R as the quantity fully characterising a given radiator. In a smooth waveguide

Card
2/5

80587

8/109/60/005/06/012/021

E140/E163

Millimeter-Band Investigation of Waveguide Radiators Excited by
Relativistic Electron Streams

the radiation resistance reaches appreciable levels and therefore the radiation in such a waveguide may be observed experimentally without difficulty. For a Cherenkov radiator with a long dielectric delay structure it is difficult to realise synchronism simultaneously at several beam harmonics. It is therefore useful to employ ferrite delay systems permitting regulation of the phase velocities of various waves by magnetic bias of a constant longitudinal magnetic field. The maximum radiation resistance in the Cherenkov radiator at a given frequency occurs for a channel diameter coinciding with the beam diameter and a waveguide diameter calculated from the condition of synchronism for the E_{01} -wave.

For the undulator maximum power is radiated at transverse dimensions of the rectangular waveguide equal to the beam width and the sum of the electron oscillation amplitude and the beam thickness respectively. The optimum design of a smooth waveguide radiator corresponds to a waveguide diameter equal to the electron beam diameter (not below

Card
3/5

20587

8/109/60/005/06/012/021
E140/E163

Millimeter-Band Investigation of Waveguide Radiators Excited by
Relativistic Electron Streams

critical). The length of synchronised radiators is taken equal to $L = 10$ cm. At this length the efficiency of synchronised radiators is substantially higher than the efficiency of non-synchronised radiators. The efficiency of the Cherenkov radiator for the present example is substantially greater than the undulator efficiency. An experimental study of these radiators was carried out using a linear electron accelerator operating in the 10 cm band with output energy 0.5 to 5 MeV and pulse current 30 to 50 mA, the tested radiator and a set of measuring instruments. The harmonic composition of the electron beam was not studied experimentally. Therefore the values of R obtained are only relative. They are somewhat low for the following reasons: the shape of the bunch at the accelerator output may differ substantially from rectangular; in calculating R reflection, absorption and conversion losses in various elements of the channel were neglected; the radiation power of the investigated

Card
4/5

84587

S/109/60/005/06/012/021

E140/E163

Millimeter-Band Investigation of Waveguide Radiators Excited by
Relativistic Electron Streams

signal sometimes reached tens of milliwatts compared with a calibration signal of 45 μ W. It was assumed that the detector characteristic is quadratic. On the average in the range from 10 to 2 mm a decrease of radiation power with decrease of wavelength was observed generally constituting approximately 1 dB per harmonic. There are 11 figures, 1 table and 16 references, of which 15 are Soviet and 1 is English.

SUBMITTED: August 20, 1959

Card 5/5

37100

S/056/62/042/004/006/037
B102/B104

24.7700
9.4178
AUTHORS:

Lifshits, T. M., Kogan, Sh. M., Vystavkin, A. N., Mel'nik,
P. G.

TITLE:

Some effects induced by r-f irradiation in n-type indium
antimonide

PERIODICAL:

Zhurnal eksperimental'noy i teoreticheskoy fiziki, v. 42,
no. 4, 1962, 959-966

TEXT: Some effects were studied which arise in n-type InSb at 4.2°K when irradiated with r-f electromagnetic waves of the mm-band. The samples were placed in a helium kryostat between the pole-pieces of an electromagnet and were irradiated by $75 \cdot 10^9$ cps modulated with 1000-cps square pulses; the irradiation intensity was $\sim 10^{-5}$ w/cm². The carrier concentration in the samples at 80°K was $6.5 \cdot 10^{14}$ cm⁻³; their mobility was $4 \cdot 10^4$ cm²/v·sec. The volt-ampere characteristics were taken at several transverse magnetic field strengths; in not too weak electrical fields the conductivity increases with the field, a fact which agrees with the assumption that in

Card 1/3

Some effects induced by r-f ...

S/056/62/042/004/006/037
B102/B104

n-type InSb scattering from ionized impurities is predominant at 4.2°K. In weak fields the characteristics are nonlinear; the authors restrict themselves to positive nonlinearities, characterized by

$\beta = [\sigma(E)]^{-1} d\sigma/dE^2$, σ being the conductivity. The emf observed is studied in connection with the following effects: (a) The bolometric effect (heating of the sample by irradiation): no indication. (b) Impurity photoeffect: no indication. (c) Effects at the contacts and the crystal grain boundaries: Effects are unclear; it is improbable that they play a role. (d) Heating of the electron gas by irradiation (change of the energy distribution of the conduction electrons): The emf signal observed in non-zero magnetic field and $v = 0$ (which cannot be attributed to an impurity photoeffect) is due to an electron-temperature gradient and can be considered as a kind of Nernst-Ettingshausen effect. Semiquantitative estimates and theoretical considerations lead to conclusion that, with and without magnetic field, the emf observed is indeed an "electronic" emf, caused by different electron temperatures at the crystallite faces. There are 7 figures.

ASSOCIATION: Institut radiotekhniki i elektroniki Akademii nauk SSSR
(Institute of Radio Engineering and Electronics of the Academy of Sciences USSR)

Card 2/3

Some effects induced by r-f ...

S/056/62/042/004/006/037
3102/3104

SUBMITTED: November 4, 1961

Card 3/3

S/120/63/000/001/059/072
E039/E420

AUTHORS: Vystavkin, A.N., Mel'nik, P.G.

TITLE: An input cascade for measuring small emf's from a low resistance source

PERIODICAL: Priory i tekhnika eksperimenta, no.1, 1963, 189-190

TEXT: In order to investigate the noise properties of semi-conductors at low temperatures and for other similar investigations it is necessary to measure extremely small emf's of the order of 10^{-10} V from a low resistance source. A design for the input cascade to a close coupled RF amplifier having an equivalent noise resistance of 200 to 300 ohms is described. This input cascade is placed inside one electrostatic and two magnetic shields. The latter consist of a lead and a steel cylinder. The whole cascade is immersed in liquid helium in the immediate neighbourhood of the sample on which noise measurements are being carried out. A reduction of 60 to 70% in the magnetic field is effected by the steel cylinder and the remainder is removed by the lead which is superconducting at the liquid helium temperature. The results show a linear relationship between the square of the emf and the

Card 1/2

S/120/63/000/001/059/072

E039/E420

An input cascade ...

resistance. This input cascade is suitable for measuring the emf of thermal noise in a resistance of 20 ohms at 4.2°K or a sinusoidal emf of 5 to 7 x 10⁻¹¹ V. This is equivalent to the emf of thermal noise in a resistance of 0.3 ohm at room temperature. There is 1 figure.

SUBMITTED: April 7, 1962

Card 2/2

I. 10369-63 EWT(1)/BDS/EEC(b)-2--AFFTC/ASD/ESD-3--P1-4--IJP(C)

ACCESSION NR: AP3000997

8/0109/63/008/006/0994/1001

AUTHOR: Vystavkin, A. N.; Kogan, Sh. M.; Lifshits, T. M.; Mel'nik, P. G. 64

TITLE: Electronic thermomagnetic effect 21

SOURCE: Radiotekhnika i elektronika, v. 8, no. 6, 1963, 994-1001

TOPIC TAGS: Electronic thermomagnetic effect, InSb single crystal specimen, electron concentrations, magnetic field, liquid helium temperature, cavity resonator, sensitivity, radiated power

ABSTRACT: The electronic thermomagnetic effect in InSb n-type single crystal specimens has been investigated. Specimens (5 x 5 x 0.8 mm) with an electron concentration of 10^{14} cm^{-3} and a mobility of 0.5×10^4 to $5 \times 10^4 \text{ cm}^2/\text{v} \cdot \text{sec}$ at $T_{\text{sub } 0} = 4.2\text{K}$ (without magnetic field) were inserted into a cavity cooled by liquid helium. A generator provided a signal of 75 Gc and was modulated by a 1 kc square wave. The appearance of an emf across the specimen terminals caused by the applied signal was observed only in the presence of a permanent magnetic field. With an increase in the intensity of the magnetic field the emf also increased and at H approximately

Card 1/2

L 10369-63
ACCESSION NR: A73000997

equal to 1700 oe , reached its maximum and then dropped again. It follows from the amplitude characteristics obtained that the photoresponse of the electronic thermomagnetic effect remains linear up to the signal level of $2 \times 10^{\text{sup } -4} \text{ w}$. Sensitivity was determined to be 500 v/w for specimens with carrier concentration of $10^{\text{sup } 14} \text{ cm}^{\text{sup } -3}$. The noise level of samples within the limits of measurement accuracy (plus or minus 50%) was found to be equal to the internal thermal resistance noise of the specimens. Consequently, the minimum detected radiated power with a signal-to-noise ratio equal to unity was $2 \times 10^{\text{sup } -13} \text{ w}$. The inertia of the electronic thermomagnetic effect, which is determined by the transfer time of excessive electron energy to the lattice, was found to be less than or equal to $3 \times 10^{\text{sup } -7} \text{ sec}$. It was noted that the described effect depends very little on the frequency and could therefore be observed during bombardment of the specimen by radiation over a broad spectrum. Orig. art. has: 4 figures and 23 formulas.

ASSOCIATION: none

SUBMITTED: 12Feb63 DATE ACQ: 01Jul63

ENCL: 00

SUB CODE: 00

NO REF SOV: 004

OTHER: 001

Card 2/2 ch/ku

ETKIN, Valentin Semenovich; GERSHENZON, Yevgeniy Mikhaylovich.
Prinimali uchastiye LAVUT, A.P.; LYUBIMOVA, T.F.; SOINA,
N.V.; KHOTUNTSEV, Yu.L.; ROZHKOVA, G.I.; KARVAKOVA, Ye.S.;
STRUKOV, I.A.; VISTAVKIN, A.N., retsenzent; ARONOV, V.L.,
retsenzent; MASHAROVA, V.G., red.

[Superhigh-frequency parametric systems using semiconductor
diodes] Parametricheskie sistemy SVCh na poluprovodnikovyykh
diodakh. Moskva, Sovetskoe radio, 1964. 351 p.
(MIRA 17:11)

L 5143-66 EWT(d)/EWT(1)/EWA(h)
ACCESSION NR: AP5026910

UR/0109/65/010/010/1907/1909
621.375.933.029.65

AUTHOR: Berlin, A. S.; Vizel', A. A.; Vystavkin, A. N.; Popov, Ye. I.;
Khotuntsev, Yu. L.; Shtykov, V. D.

34
B

TITLE: Parametric amplification in the 8-mm band

SOURCE: Radiotekhnika i elektronika, v. 10, no. 10, 1965, 1907-1909

TOPIC TAGS: parametric amplification, millimeter wave

ABSTRACT: In recently published articles (B. C. DeLoach, Proc. IEEE, 1963, 51, 8, 1153 and others) on millimeter-band semiconductor amplifiers, no characteristics have been reported. The present article describes the design and characteristics of and indicates an application for an 8-mm-band parametric amplifier. Coaxial-design epitaxial germanium diodes with 0.04--0.08-pf capacitance and 3--5-v reverse voltage were used in most experiments; critical frequency at a bias of -3 v was 280--430 Gc. The diodes operated as amplifiers at a low pumping power and an operating-point bias of 0.5--2 v. The diodes were tested within -60+85C; up to +60C, the leakage current at -1.5 v was 1 μ amp or less. The new diodes were tested in a single-cavity 8-mm parametric amplifier (see Fig. 1 of Enclosure). The signal is applied via a tapered waveguide matching unit 1. Behind the diode 4, a short-circuiting section 2 is arranged whose length equals an odd number of

Card 1/3

02810-61

L 5143-66
ACCESSION NR: AP5026910

quarter-waves. The amplifier is tuned by a short-circuiting line 3 that has a characteristic resistance of 100 ohm. Transformer 5 serves for adjusting the coupling. With a gain of 20 db, the passband was 78 Mc and the noise temperature, $600 \pm 150K$. The parametric amplifier was used in a modulation-type radiometer whose fluctuation sensitivity was measured. Orig. art. has: 3 figures and 2 formulas. 0

ASSOCIATION: none

[03]

SUBMITTED: 23Jan65

ENCL: 01

SUB CODE: EC.

NO REFO SOV: 002

OTHER: 003

ATD PRESS: 4134

Card 2/3

L 5143-66

ACCESSION NR: AP5026910

ENCLOSURE: 01




Fig. 1. A parametric semiconductor amplifier for the 8-mm band

Card 3/3

VERKHOVSKAYA, Z.N.; VYSTAVKINA, L.B.; KLIMENKO, M.Ya.; TEVLINA, A.S.;
TROSTYANSKAYA, Ye.B.

Coarse-grained ion exchangers as catalysts of the hydration
of olefins and dehydration of alcohols. Khim.prom. no.4:248-
250 Ap '62. (MIRA 15:5)
(Ion exchange resins) (Hydration) (Dehydration (Chemistry))

YESTAVKIN, N.I.; RESHETOV, M.; BARKOV, Yu.A.

Readers' letters. Bezop. truda v prom. 8 no.10:56 0 '64. (MIRA 17:11)

1. Pomoshchnik glavnogo inzhenera po tekhnike bezopasnosti shakhty im. Oktyabr'skoy revolyutsii tresta Shakhtantratsit kombinata Rostovugol' (for Barkov).

VYSTAVKIN, P. S.

Afforestation - Kursk (Province)

Close planting of oak in spots in the "Dedovo-Veseloe woods." Les 1 step
4, No. 2, 1952.

Monthly List of Russian Accessions, Library of Congress , June 1952
Unclassified.